


RIM TUBE MULTIPLE ROUND



PENDANT
STATIC WHITE



Project: _____
Type: _____



DESCRIPTION

Rim Tube introduces a refined tubular form to the Rim Collection with its minimalist 1.4" diameter. This versatile luminaire delivers bold expression through its clean geometry and striking illumination. Available in multiple shapes, configurations and sizes. Rim Tube maintains the signature sleek and minimalist aesthetic of the Rim family, scaling from simple geometric shapes to sculptural, multidimensional installations.

Order Guide

LUMINAIRE ID	SIZE	OPTIC	LIGHT SOURCE ¹	CRI
RIMTUMRP		ULO	SW	90CRI
RIMTUMRP - Rim Tube Multiple Round Pendant	2 RINGS	ULO - Uniform Lambertian Optic	SW - Static white ¹ Chromawerx SOLA, DUO, and QUADRO also available. Consult factory.	90CRI - 90+ CRI
	24IN+36IN - Ø 24" + Ø 36"			
	24IN+48IN - Ø 24" + Ø 48"			
	36IN+48IN - Ø 36" + Ø 48"			
	36IN+60IN - Ø 36" + Ø 60"			

LUMEN PACKAGE			COLOR TEMPERATURE			VOLTAGE	REMOTE DRIVER	ELECTRICAL ⁴	
								1C	
2 RINGS			3 RINGS			27K - 2700K 30K - 3000K 35K - 3500K 40K - 4000K 50K - 5000K	120V - 120V 277V - 277V UNV - 120V-277V 347V ² -347V	D1 - 1% 0-10V DA ³ - DALI LDE1 ³ - Lutron Hi-Lume 1% Eco ELD1 - eldoLED 1% EC0drive 0-10V ELDO - eldoLED0.1% SOLOdrive 0-10V	1C - 1 circuit
Low	High		Low	High					
24"+36"	5000LM	7500LM	12"+18"+24"	4500LM	6700LM				
24"+48"	6000LM	9000LM	12"+24"+36"	6000LM					
36"+48"	7000LM	10500LM	24"+36"+48"	9000LM	13500LM				
36"+60"	8000LM	12000LM	36"+48"+60"	12000LM	18000LM				
48"+60"	9000LM	13500LM							
							² Available with D1 driver only.	³ On-site commissioning is required.	⁴ For other circuit configurations, consult factory.


MOUNTING	FINISH														
RDB	SC														
DRIVER BOX ⁵ RDB ⁶ - Remote driver box ⁵ For more information see page 3. ⁶ Multiple remote driver boxes may be necessary for lumen packages higher than 10000 lm.	CANOPY FINISH W - Matte white AL - Aluminum B - Matte black CF# - Custom finish, specify RAL# POWER POC - Power-over-aircraft cable BAC - Black power cord + aircraft cable WAC - White power cord + aircraft cable MOUNTING POINTS SC - Single canopy MOUNTING CABLE LENGTH ⁷ 18IN - 18" 24IN - 24" 36IN - 36" 48IN - 48" 60IN - 60" 72IN - 72" 96IN - 96" 120IN - 120" #IN - Specify nominal length in inches ⁷ Minimum mounting heights are based on the size of the ring on top (closest to ceiling) of the stack. <table border="1"> <thead> <tr> <th>Fixture size</th><th>Minimum height</th></tr> </thead> <tbody> <tr><td>Ø 12"</td><td>8"</td></tr> <tr><td>Ø 18"</td><td>11"</td></tr> <tr><td>Ø 24"</td><td>15"</td></tr> <tr><td>Ø 36"</td><td>22"</td></tr> <tr><td>Ø 48"</td><td>29"</td></tr> <tr><td>Ø 60"</td><td>36"</td></tr> </tbody> </table>	Fixture size	Minimum height	Ø 12"	8"	Ø 18"	11"	Ø 24"	15"	Ø 36"	22"	Ø 48"	29"	Ø 60"	36"
Fixture size	Minimum height														
Ø 12"	8"														
Ø 18"	11"														
Ø 24"	15"														
Ø 36"	22"														
Ø 48"	29"														
Ø 60"	36"														
	W - Matte white AL - Aluminum B - Matte black CF# - Custom finish, specify RAL#														

RIM TUBE MULTIPLE ROUND




PENDANT
STATIC WHITE

Dimensions




Size	Ø Diameter
Ø 12"	Ø 14 1/8"
Ø 18"	Ø 20 1/8"
Ø 24"	Ø 26 1/8"
Ø 36"	Ø 38 1/8"
Ø 48"	Ø 50 1/8"
Ø 60"	Ø 62 1/8"

SECTION VIEW



Photometrics

Delivered lumens at 4000K at 90+ CRI



Ø 12"

LM	W	LM/W
1000	11.1	90
1500	17.2	87

Ø 18"

LM	W	LM/W
1500	16.7	90
2250	25.9	87

Ø 24"

LM	W	LM/W
2000	22.2	90
3000	34.6	87

Ø 36"

LM	W	LM/W
3000	33.4	90
4500	52	87

Ø 48"

LM	W	LM/W
4000	44.5	90
6000	69.2	87

Ø 60"

LM	W	LM/W
5000	55.6	90
7500	86.2	87


MULTIPLIER TABLE

Use this table to get results for different color temperatures for all photometric tables.

CCT	WATTS	LPW
2700K	1.08	0.92
3000K	1.05	0.96
3500K	1.02	0.98
4000K	1.00	1.00
5000K	1.00	1.00

Mounting Options

- RDB - REMOTE DRIVER BOX
- SC - SINGLE CANOPY



AC - Aircraft cable

POC - Power-over-aircraft cable

*Minimum height

For single canopy option, the minimum required mounting heights:

Fixture size * Minimum height	
Ø 12"	8"
Ø 18"	11"
Ø 24"	15"
Ø 36"	22"
Ø 48"	29"
Ø 60"	36"

RIM TUBE MULTIPLE ROUND



PENDANT
STATIC WHITE

Technical Specifications

OPTIC

Uniform Lambertian Optic (ULO)

Thermoformed from impact-modified white PMMA, the ULO provides even luminosity, with up to 88% transmission. Combined with the LED array running around the inside of the housing, the open form and ULO create a widespread 50% inward and 50% outward light distribution with spacing criteria of 1.6.

LIGHT SOURCE

Custom array of mid-flux LEDs are mounted directly to the housing for optimal thermal performance. Available in 2700K, 3000K, 3500K, 4000K, and 5000K with 90+ CRI and elevated R9 value. Color consistency is maintained to 3 SDCM.

All LEDs have been tested in accordance with IESNA LM-80-08 and results have shown L80 lumen maintenance are greater than 60,000 hours. Absolute product photometry is measured and presented in accordance with IESNA LM-79, unless otherwise indicated.

ELECTRICAL

Factory-set, adjustable output current LED driver with universal (120-277VAC) input. Dimmable from 100% to 1% with 0-10V dimming control. Rated life (90% survivorship) of 50,000 hours at 50°C max. ambient (and 70°C max. case) temperature. At maximum driver load: Efficiency > 84%, PF > 0.9, THD < 20%. Other specifiable options include Lutron Hi-Lume 1% Eco, eldoLED 1% ECOdrive 0-10V, eldoLED 0.1% SOLOdrive 0-10V, and DALI protocol drivers. All of our standard 0-10V drivers are NEMA 410 compliant.

PoE

Depending on the PoE manufacturer selected, Lumenwerx will install the node in factory as either integral to the luminaire or as a remote module. Factory programming of the PoE node may or may not enable the following functionalities: lumen package, DUO (tunable white), QUADRO (RGBW), emergency battery backup, and sensor integration. These must be addressed and evaluated on a case-by-case basis.

FINISH

Interior: 95% reflective, matte white powder coating

Exterior: Matte white, matte black or aluminum powder coating. Custom finishes are also available.

CONSTRUCTION

Housing: Rolled and seamlessly welded aluminum

Lens: Coextruded polycarbonate

WEIGHT

Ø 12": 2.3 lbs - 1 kg

Ø 18": 3.5 lbs - 1.6 kg

Ø 24": 4.7 lbs - 2.1 kg

Ø 36": 7.1 lbs - 3.2 kg

Ø 48": 9.4 lbs - 4.3 kg

Ø 60": 11.8 lbs - 5.3 kg

CERTIFICATION

ETL: Rated for indoor dry/damp locations. Conforms to UL Standard 1598 and certified to CAN/CSA Standard C22.2 No. 250.0.

WARRANTY

Lumenwerx provides a five-year limited warranty on electrical and mechanical performance of the luminaires, including the LED boards, drivers, and auxiliary electronics. Lumenwerx will repair or replace defective luminaires or components at our discretion, provided they have been installed and operated in accordance with our specifications. Other limitations apply, please refer to the full warranty on our website.